Techninė specifikacija:

IP Video Input	4-ch
Two-way audio input	1-ch, RCA (2.0 Vp-p, 1kΩ)
Incoming bandwidth	40Mbps
Outgoing bandwidth	80Mbps
VGA Output	1- ch, resolution: 1920*1080P/60Hz, 1280*1024/60Hz, 1280*720/60Hz, 1024*768/60Hz
HDMI Output	1- ch, resolution: 4K(3840*2160)/60Hz, 4K(3840*2160)/30Hz, 1920*1080P/60Hz, 1600*1200/60Hz, 1280*1024/60Hz, 1280*720/60Hz, 1024*768/60Hz
Recording resolution	8MP/6MP/5MP/4MP/3MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Audio Output	1-ch, RCA (Linear, 1kΩ)
Live view / Playback	8MP/6MP/5MP/3MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Capability	4-ch@1080P
SATA	1 SATA interface for 1 HDD
Capacity	Up to 6TB capacity for each disk
Network Interface	1 RJ-45 10 / 100 Mbps selfadaptive Ethernet interface
USB Interface	2 USB 2.0 Interfaces
PoE Interface	4 independent 10 /100 Mbps PoE Ethernet interfaces
Power Supply	48 VDC
Consumption (without hard disk)	≤ 10 W
Working Temperature	0 ºC ~ +40 ºC (+32 ºF ~ +104 ºF)
Working Humidity	10%~90%
Chassis	315 mm chassis
Dimensions (W x D x H)	315 × 240 × 48 mm (12.4\" × 9.4\" × 1.9\")
Weight (without hard disk)	≤ 1 Kg