


- Installing batteries before first use .
- Before connecting the APP, the product only can be locked or opened by password "123456", and other passwords are invalid .
- Connecting APP : (All operations in the APP, need to turn on the Bluetooth of mobile phone)
  1. Downloading TT Lock APP on the mobile, and opening the APP to register and log in .
  2. Turning on Bluetooth .
  3. Pressing any key of the safe box panel to make the key light on .
  4. Adding safe box for the first time : Clicking "+" → "All Locks" → "FY01" → Rename → Confirm (This step can only be operated when Bluetooth is on and the key light is on) .
  5. Adding a new safe box again : clicking " ( ≡ ) " in the top left corner → "Add Lock" → "All Locks" → "FY01" → Rename → Confirm (This step can only be operated when Bluetooth is on and the key light is on) .
- Locking the safe box :  
Entering "4-9" digits password and pressing "Lock" to lock .
- Opening the safe box:  
Entering correct password and pressing "Lock" to open .
- Changing the management password ( Ex-factory management code:123456 )
  1. Opening the TT Lock APP .
  2. Clicking "Settings" (If multiple safe boxes have been added, select the safe box to be changed first) .
  3. Clicking "Basic Information" .
  4. Clicking "Administrator Unlocking Password" .
  5. Clicking "Password" .
  6. Entering "6-9" digits new management password to confirm .
- Opening the safe box with management password :  
When the safe box is locked, enter the management password and press the "Lock" key .
- Using TT Lock APP to open and lock the safe box :  
Click "  " to open the box (long press 2 seconds to lock the box) .
- Authorizing other TT Lock users to open the safe box :
  1. Selecting the safe box .
  2. Clicking "Electronic Key".
  3. Clicking "Send Key".
  4. Following your requirements to select temporary, permanent, date, time, etc and sending the key .
  5. Entering the phone number of the receiver and click "send" .
  6. Receiver can open the safe box by the electronic key received .
- Using temporary password to open the safe box :
  1. Selecting the safe box .
  2. Clicking the password .
  3. Clicking " obtain the password " .
  4. Following your requirements to select temporary, permanent, date, time, etc., and clicking " obtain the password " .
  5. Clicking " share ", selecting the sending mode and sending the password to the receiver .
  6. Receiver can open the safe box by the temporary password received .
- Using card to open and lock the safe box :
  1. Selecting the safe box .
  2. Clicking "Card".

3. Clicking "Add Card" .
4. Entering the card name and clicking "OK", the safe box screen lights up .
5. Placing the card in the induction position, when the safe box makes a drip sound ,then the card is added successfully .
6. Placing the card in the induction position , the safe box will be opened or locked .